

GLASS KILNS

Tucker's Cone Art glass kilns are second to none when it comes to performance, quality and service. We use only the best raw materials and expert craftsmanship to produce the best kilns available, and we've been doing it since 1982. Many of the Cone Art glass kiln models are available in both 9" and 13.5" depths. Every Tucker's Cone Art Glass Kiln is certified and approved by CSA / CUL for Canada and the U.S.A., and CE for Europe. Compare a Cone Art to any other kiln on the market. Nobody can match us feature for feature.



B3K117G



B3K115G SQ




V62309G
(Shown with optional lid-lifter)



B3K2309G SQ

STANDARD FEATURES



Lid Elements



Easy Access Panel



*Sectional Design



Technical Support



Energy Savings



V62813G
(Shown with optional lid-lifter)

V64213G

AVAILABLE ADD-ONS



CONTROLLER OPTIONS



B3K2309G SQ

GLASS KILN SPECIFICATIONS

| | Model | Dimensions (inches): w (x l) x h Inside Outside | Sections | Cubic Feet | Ship Weight (lbs) | Phase | Amps 240V 208V | Breaker Rqd** | CU Wire GA (AWG) | kW |
|--------|----------|--|----------|---------------|-------------------------|-------|---------------------|------------------|------------------------|------|
| ROUND | 117G | 14.5 x 6 19.5 x 12 | 1 | 1 | 130 | 1 | 14.5 (120V) | 15A | 14 | 1.7 |
| | 1809G | 17.5 x 9 24.5 x 14 | 1 | 1.3 | 200 | 1 | 28 32 | 40A | 8 | 6.7 |
| | 1813G | 17.5 x 13.5 24.5 x 18.5 | 2 | 2 | 200 | 1 | 28 32 | 40A | 8 | 6.7 |
| | 2309G | 23.5 x 9 28.5 x 14 | 1 | 2.3 | 220 | 1 | 30 35 | 40A | 8 | 7.2 |
| | 2313G | 23.5 x 13.5 28.5 x 19.5 | 2 | 3.4 | 250 | 1 | 30 35 | 40A | 8 | 7.2 |
| | 2809G | 28 x 9 34 x 15 | 1 | 3.3 | 270 | 1 | 42 48 | 60A | 6 | 10.1 |
| | 2813G | 28 x 13.5 34 x 19.5 | 2 | 5 | 305 | 1 | 42 48 | 60A | 6 | 10.1 |
| OVAL | 4209G | 41 x 31 x 9 47 x 37 x 15 | 1 | 5.5 | 375 | 1 | 48 55 | 60A | 6 | 11.5 |
| | 4213G | 41 x 31 x 13.5 47 x 37 x 19.5 | 2 | 8.25 | 415 | 1 | 48 55 | 60A | 6 | 11.5 |
| SQUARE | 115G SQ | 15.5 x 15.5 x 6.5 24 x 30 x 12 | 1 | 0.9 | 130 | 1 | 18 (120V) | 20A | 12 | 2.2 |
| | 2309G SQ | 23 x 23 x 9 35 x 41 x 15 | 1 | 2.3 | 220 | 1 | 30 35 | 40A | 8 | 7.2 |
| | 2313G SQ | 23 x 23 x 13.5 35 x 41 x 19.5 | 2 | 3.45 | 250 | 1 | 30 35 | 40A | 8 | 7.2 |

ELECTRICAL NOTES

Install a minimum of 12" from any combustible surface. Fire only on stand provided. Breaker sizes are recommendations only - consult your local electrical code and have the kiln installed by a certified electrician.

All 240 / 208 Volt models come with an 8' SOOW cable with bare wire end and are intended to be hardwired directly to a breaker or disconnect switch. All 240 / 208 Volt models utilize hot lines and a ground (no neutral wire). The model 117G (120 Volts) comes with a 15 Amp, 125 Volt plug (NEMA 5-15P) on a 6' cable. The model 115G SQ (120 Volts) comes with a 20 Amp, 125 Volt plug (NEMA 5-20P) on a 6' cable.